



TECHNICAL DATA SHEET BASE OIL SN 150 (TYPE 3)

Note: PUB-LTD Base oil is categorized in group I. It's the common quality base oil product whith different applications in the industry. It packed in new or used 180 kg drums, iso tank, flexi tanks and bulk shipments. Each 20 foot container takes 80 drum.

No	Specification	Result		
		Min	Max	Test Method
1	KINEMATIC VISCOSITY @100°C	6	6.5	ASTM D 445
2	KINEMATIC VISCOSITY @40°C	37	42	ASTM D 445
3	FLASH POINT °C	205	215	ASTM D 92
4	VISCOSITY INDEX	100	110	ASTM D 2270
5	POUR POINT	0	0	ASTM D 97
6	COLOR	1	1.5	ASTM D 1500
7	TOTAL ACID NUMBER mgKOH/ g	0	0.03	ASTM D 664
8	DENSITY	0.873	0.875	ASTM D 1298

^{• 703,} Damac Executive Bay, Tower B, Al A'amal St. Business Bay, Dubai, United Arab Emirates

^{• 220,} Sinpas Altınoran Tower 2, Galip Erdem St. Çankaya, Ankara, Turkey

[⊕] www.publtd.com

info@publtd.com

O+971 4 878 2031 (UAE Office)

^{• +90 530 118 73 92 (}Turkey Office)