TECHNICAL DATA SHEET
Oxidized Bitumen Grade 75/30

Note: Oxidized Bitumen is a peculiar amorphous material that is generally in liquid form when discharged by oxidation plants at a temperature ranging from 240 to 300°C, and becomes solid or pasty at ambient temperatures. While being relatively hot, it is viscous, whereas when in a pasty or solid state it possesses a fair degree of elasticity. Both in liquid and in plastic or solid form oxidized bitumen is a highly insulating material with good adhesion properties concerning almost any solid material. Oxidized Bitumen is also known as blown asphalt, hard bitumen, hard asphalt, blown bitumen.

Specification	Result	Test Method
Specific Gravity @25/25 C	1.05 approx.	D-70
Penetration @25C	25/35	D-5
Softening Point C	70/80	D-36
Ductility @25C	1.5 min	D-113
Loss On Heating (Wt)%	0.2 max	D-6
Flash Point C	260 min	D-92
Solubility in CS2 (Wt)%	99 min	D-4

703, Damac Executive Bay, Tower B, Al A'amal St.
Business Bay, Dubai, United Arab Emirates

14A, 538. Cad, karsıyaka mah, gölbası,
Ankara, Turkey

www.publtd.com
info@publtd.com
+971 4 878 2031 (UAE Office)
+90 530 118 73 92 (Turkey Office)